


UT-056-STR

Semi-Rigid Coaxial Cables



The 50Ω copper semi-rigid cables from Micro-Coax offer exceptional performance with minimal signal loss and low VSWR across the operating frequency. These versatile cables are engineered with high shielding effectiveness to reduce signal loss and interference, making them ideal for today's demanding applications.

Details and Materials



Impedance 50 Ohms	Operating Temperature -55°C to +175°C	RoHS Compliant
-----------------------------	---	--------------------------

Dimensions

Outer Conductor Diameter	in	0.056
	mm	1.422
Center Conductor Diameter	in	7 x 0.0312
	mm	7 x 0.7925
Length (Maximum)	ft	20
	m	6.10

Mechanical Characteristics*

Outer Conductor Integrity Temp.	°C	200
Inside Bend Radius (Minimum)	in	0.063
	mm	1.600
Weight	lbs/100ft	0.72
	kg / 100m	1.08

Electrical Characteristics*

Capacitance	pF/ft	29.0
	pF/m	95.2
Corona Extinction Voltage	VRMS @60 Hz	1000
Voltage Withstanding	VRMS @60 Hz	3000
Higher Order Mode Frequency	GHz	111.0

Power (@ 20 °C, Maximum)

GHz	Watts Cw
0.5	107.3
1.0	75.4
5.0	33
10.0	23
18.0	16.8
26.5	13.6
40.0	10.9
50.0	9.6
65.0	8.3
90.0	6.9

Attenuation (Typical)

GHz	dB/100 ft
0.5	24.7
1.0	35.2
5.0	81
10.0	117
18.0	160.8
26.5	199
40.0	250.6
50.0	284.6
65.0	331.2
90.0	400.9

* Applicable at room temperature. Contact for performance over temperature range.

MICRO-COAX
 AN AMPHENOL COMPANY